

# SymphoniePLUS<sup>3</sup>

15-channel data logger



## CONTINUOUS IMPROVEMENT HAS ITS REWARDS

### Key Features:

- **Universal Anemometer Channels**
  - Six counter channels accommodate the anemometer brand of your choice.
  - Counter channels do not require SCM cards.
- **One-second Sample Rate**
  - Conforms to IEC 61400-12-1.
- **Three 'Flex' Channels**
  - Flex channels configure automatically based on SCM installed.
  - Allows for numerous sensor configuration options.
- **Password Protected Access**
  - Unauthorized user lockout prevents access to logger via the keypad.

Systems | Sensors | Data Loggers | Turbine Control Sensors | Communications | Lidar | Condition Monitoring Systems

SEE THE POTENTIAL™

Renewable NRG Systems | Hinesburg, Vermont 05461 | USA 802.482.2255 | [www.renewablenrgsystems.com](http://www.renewablenrgsystems.com)



# SymphoniePLUS<sup>®</sup>3

## 15-channel data logger

### Specifications

#### Description

<b>Instrument type</b>	15 channel internet-enabled wind energy data logger
<b>Applications</b>	<ul style="list-style-type: none"> <li>• Wind resource assessment</li> <li>• Turbine power performance verification</li> </ul>
<b>Sensor compatibility - counter channels</b>	<ul style="list-style-type: none"> <li>• NRG Class 1 anemometer</li> <li>• NRG #40C anemometer</li> <li>• Opto anemometer</li> <li>• Reed switch anemometer</li> </ul>
<b>Sensor compatibility - analog channels</b>	<ul style="list-style-type: none"> <li>• NRG Systems #200P direction vane</li> <li>• NRG Systems #110S temperature sensor</li> <li>• Li-Cor #200SZ pyranometer</li> <li>• NRG Systems #BP20 absolute pressure (requires optional iPack power)</li> <li>• RH-5X relative humidity (requires optional iPack power)</li> </ul>
<b>Counter channels</b>	<p>Channels 1-3 and 13-15 are counter inputs</p> <ul style="list-style-type: none"> <li>• Channels 1-3 and 13-15 are pre-programmed for NRG Class 1 / NRG #40C anemometers or compatible</li> <li>• Maximum counter input frequency: 2500 Hz</li> </ul>
<b>Analog channels</b>	<p>Channels 7-12 are analog inputs</p> <ul style="list-style-type: none"> <li>• Channels 7 and 8 are dedicated for NRG #200P direction vane</li> <li>• Channels 9-12 use analog Signal Conditioning Modules (SCMs) to configure each channel for a particular sensor</li> </ul>
<b>Flex channels</b>	<p>Channels 4-6 are 'Flex' channels</p> <ul style="list-style-type: none"> <li>• Analog OR counter inputs</li> <li>• Accept Signal Conditioning Modules (SCMs) to configure the channel for a particular sensor type</li> </ul>

#### Data Collection

<b>Sampling interval</b>	One second
<b>Averaging interval</b>	10 minute, fixed
<b>Real time clock</b>	Internal battery-backed
<b>Storage medium</b>	SD Card, non-volatile FLASH
<b>Maximum data storage</b>	672 files
<b>Parameters recorded for each channel</b>	<p>Each data interval is time/date-stamped:</p> <ul style="list-style-type: none"> <li>• Average</li> <li>• Standard deviation</li> <li>• Min*</li> <li>• Max*</li> </ul> <p>*min and max not used for wind direction vanes</p>
<b>File format</b>	<ul style="list-style-type: none"> <li>• Windows compatible</li> <li>• (1) 14 KB binary file per day</li> <li>• Header includes site, serial number and sensor information</li> </ul>
<b>Software</b>	<p>Symphonie Data Retriever (SDR) for Windows</p> <ul style="list-style-type: none"> <li>• Scales raw data</li> <li>• Creates measurement database for each site</li> <li>• Creates basic reports</li> <li>• Maintains site and sensor information</li> <li>• Configures iPacks</li> </ul>
<b>Reader</b>	Windows compatible SD Card reader
<b>Data delivery</b>	<ul style="list-style-type: none"> <li>• SD Card</li> <li>• Internet email via GSM, CDMA, or Iridium Satellite with optional iPack</li> </ul>

#### Resolution

<b>Analog measurement</b>	0.1% of full scale (1024 counts)
<b>Counter average</b>	0.1% of the value stored
<b>Analog average</b>	0.1% of the value stored
<b>Min / Max stored</b>	0.4% of the value stored
<b>Standard deviation</b>	4% of the value stored

#### Configuration

<b>User interface</b>	<ul style="list-style-type: none"> <li>• Liquid Crystal Display (LCD) 4 x 20 characters</li> <li>• 16 key pad (6 navigation keys plus numeric/phone pad) with audible feedback</li> </ul>
<b>Configurable parameters</b>	<ul style="list-style-type: none"> <li>• Clock</li> <li>• Time zone</li> <li>• Site number</li> <li>• Display scaling (defaults are provided for each channel based on channel type)</li> </ul>
<b>iPack options</b>	<ul style="list-style-type: none"> <li>• iPack configured via serial port connection to your PC</li> <li>• Serial connection direct to iPack or through logger's iPack access port</li> <li>• Symphonie Data Retriever for Windows integrates iPack settings</li> </ul>

#### Connections

<b>Sensor wiring</b>	<ul style="list-style-type: none"> <li>• Sensors connect to removeable field wiring panel</li> <li>• Field wiring panel plugs into logger</li> <li>• Ground stud connects to earth ground with included ground cable</li> </ul>
<b>Expansion slots</b>	<ul style="list-style-type: none"> <li>• Three (3) 'Flex' SCM slots accept analog or counter (digital) SCMs</li> </ul>
<b>Communication ports</b>	<ul style="list-style-type: none"> <li>• Four (4) SCM slots accept only analog SCMs</li> <li>• Male DB25 interfaces to one optional iPack communications module</li> <li>• iPack access port provides a connection to the iPack programming port without dismounting the iPack or logger</li> </ul>

#### Power requirements

<b>Batteries</b>	<ul style="list-style-type: none"> <li>• Two (2) 1.5 Volt D-Cell Batteries (included)</li> <li>• Nominal voltage: 1.5 Volts</li> <li>• Minimum voltage: 0.9 Volts</li> <li>• Battery life approximately one year, depending on configuration</li> </ul>
<b>External power input</b>	<ul style="list-style-type: none"> <li>• Provided by an optional iPack</li> </ul>
<b>External solar input</b>	<ul style="list-style-type: none"> <li>• Provided by an optional iPack</li> </ul>
<b>Other</b>	<ul style="list-style-type: none"> <li>• Optional iPacks provide 12V power required by some sensors</li> <li>• PV/Battery Only iPack provides power to sensors and logger for stand alone configurations</li> </ul>

#### Installation

<b>Mounting</b>	<ul style="list-style-type: none"> <li>• Mounts with 4 bolts (included) to keyed slots inside of metal shelter box</li> <li>• Shelter box mounts to tower with hose clamps</li> </ul>
<b>Tools required</b>	<ul style="list-style-type: none"> <li>• Screwdriver for input terminals, included</li> <li>• 8 mm (5/16 inch) wrench or nut driver for logger mounting screws and ground nuts</li> </ul>

#### Environmental

<b>Operating temperature range</b>	-40°C to 65°C (-40°F to 149°F) Note: display readable -30°C to 55°C (-22°F to 130°F)
<b>Operating humidity range</b>	0 to 100% RH non-condensing
<b>Lifespan</b>	10 years +

#### Physical

<b>Weight</b>	1.3 kg (2.6 pounds), including batteries
<b>Dimensions</b>	22.2 cm (8.7") h x 18.8 cm (7.4") w x 7.7 cm (3.0") d, including field wiring panel

#### Materials

<b>Faceplate</b>	Injection molded black ABS
<b>Buttons</b>	White elastomer dome keypad
<b>Wiring panel</b>	Fiberglass-epoxy terminal board, sealed gold plated pins, zinc plated screws and terminals
<b>Enclosure</b>	Weatherproof polycarbonate

#### For more information:

Renewable NRG Sales, 802-482-2255  
110 Riggs Rd., Hinesburg, VT 05461 USA  
www.renewablenrgsystems.com