



Highly versatile, reliable and rugged routers

Available in 3G and LTE and with WAN, LAN, Wi-Fi and serial connectivity, the E220 series of M2M routers is designed for mission-critical enterprise applications.



Advanced Failover

Maximise uptime by seamlessly switching between multiple Internet interfaces

Advanced Load Balancing



Spread or bind your data traffic across the multiple Internet interfaces, based on data type, source or destination and the relative WAN connectivity costs



Multiple Tunnelling Schemes

Secure your data using a variety of VPN tunnelling schemes, including PPTP, PPTP, OpenVPN, GRE and IPsec

RS-485 Operation



Integrate sensors and third-party devices over the RS-485 serial port to provide seamless connectivity to IP networks



E220 Series specifications

HARDWARE

Material	Brushed aluminium alloy, DIN Rail mountable
Dimensions	61.25 x 85.75 x 24.5 mm without connectors
Weight	Approx. 152 g
Operating status LED x 6	Alert / Power / Cellular signal, network and activity / Wi-Fi
Operating temperature range	All Lite models: -20°C ~ +55°C All other models: -30°C ~ +70°C
SDRAM	All Lite models: 512 Mbit All other models: 1 Gbit

SOFTWARE

Administration / Network Protocols	Web-based user interface, set-up wizard, console log viewer, save / load configuration, NTP, SMS / OTA remote configuration, TR-069 capable
Redundancy	Ethernet, cellular, Wi-Fi - configurable as failover or load-balancing
Resilience	Network connectivity watchdog (configurable), internal application watchdog
Wi-Fi	Client or Access Point (approx. 40-user), multiple SSID, WEP, WPA, WPA-PSK / WPA2-PSK security modes
M2M services	Compatible with D2SPHERE™ device management services
Security	Zone-based firewall, VLAN, DMZ, HTTPS local and remote connection, SIM PIN
Performance / Fault Management	Real time processor load and interface (WAN / LAN / Wi-Fi), traffic analysis, ICMP, trace-route, NS lookup
Routing	DHCP, static routing, port-forwarding, traffic routing, static/dynamic DNS, DNS proxy, NAT, STP
VPN	PPTP client, L2TP, OpenVPN client / server / pass-through, GRE, IPsec
Industrial Protocols	Modbus RTU to TCP support, Modbus master

INTERFACES

LAN	RJ45 connector with Tx / Rx LEDs
RS-485	Full- and half-duplex, 6 kV contact, 8 kV air discharge protection / 5-pin, 2.5 mm pitch COMBICON connector
Wi-Fi	IEEE 802.11b/g/n 2T2R 2.4 GHz (max. 300 Mbps throughput) / RP-SMA antenna connector (50 Ω) x 2
WAN	RJ45 connector with Tx / Rx LEDs; switchable to LAN 2
Cellular	SMA antenna connector x 1 (E225 models) or x 2 (E224 and E228 models)
SIM	Mini SIM 1.8 V / 3.0 V Optional dual SIM operation via a factory-fitted MFF SIM
GPS*	SMA antenna connector either dedicated (E225 models) or shared with cellular diversity (E224 and E228 models)
Digital I/O x 2	Input - detection, 5 V ~ 48 V DC Output - open collector, max. output 200 mA / 3-pin, 2.5 mm pitch COMBI-CON connector with common ground

POWER

Main Source	Roadworthy** 9 V ~ 60 V DC on a 2-pin Micro-Fit™ 3.0 female connector ** Compliant with ISO 7637-2:2011 and 2004 as well as ISO 21848:2005
Alternate source*	Class 3 PD-PoE with seamless fall-back onto the main source
Last Gasp*	Approx. 5-minute via two 96 mWh Li-ion batteries (not functional below -10°C)


* Not available on Lite models

PRODUCT NAME	TERRITORIES / OPERATORS	CELLULAR TYPE	BANDS	FALL-BACK MODE	BANDS	PLANNED APPROVALS AND CERTIFICATIONS			AVAILABLE IN...	ORDER CODE
						REGULATORY	INDUSTRY	OPERATOR		
E224	EMEA	LTE cat. 1	3/8/20	2G	3/8	CE Marking	GCF		Q2 '17	E224#38K#38
E225 Lite	EMEA, Asia	3G (*)	1/8	2G	3/8	CE Marking	GCF		Q3 '16	E225LITE#02
E225	EMEA, Asia	3G (*)	1/8	2G	3/8	CE Marking	GCF		Q3 '16	E225#02
E224 Lite	Verizon Wireless	LTE cat. 1	4/13	x		FCC		Verizon Wireless		E224LITE#4D
E224 Lite	AT&T Wireless and T-Mobile USA	LTE cat. 1	2/4/12			FCC	PTCRB	AT&T Wireless T-Mobile USA		E224LITE#24C
E224	AT&T Wireless and T-Mobile USA	LTE cat. 1	2/4/12			FCC	PTCRB	AT&T Wireless T-Mobile USA		E224#24C
E228	- AT&T Wireless and Rogers (factory setting) - Verizon Wireless (user-reconfigurable to...)	LTE cat. 4	2/4/5/17 2/4/13	3G (**) x	2/5 x	FCC	PTCRB	AT&T Wireless Verizon Wireless	Q3 '16	E228#245DH#25
E228	- Telstra and Spark - Variously suited to operators in Taiwan (please contact us)	LTE cat. 4	3/7/28			RCM NCC		Telstra	Q3 '16	E228#37S
E228	NTT docomo	LTE cat. 4	1/19/21			JRF and JPA		NTT docomo	Q1 '17	E228#1JL
E228	KDDI	LTE cat. 4	1/11/18			JRF and JPA		KDDI		E228#1BI
E228	- Korea, Thailand and Brazil - Variously suited to operators in Hong Kong and the Philippines (please contact us)	LTE cat. 4	1/3/5/7			KCC ANATEL		SK telecom, kt and LG U*	Q3 '16	E228#1357
E225 Lite	World	3G (*)	1/2/5/8	2G	2/3/5/8	CE Marking	GCF		Q3 '16	E225LITE
E225	World	3G (*)	1/2/5/8	2G	2/3/5/8	CE Marking	GCF		Q3 '16	E225

Please consult us regarding the models in grey

(*) 7.2 Mbps downlink; 5.76 Mbps uplink
(**) 43.2 Mbps downlink; 5.76 Mbps uplink

Maestro Wireless Solutions Limited
9th Floor, Wing Cheong Factory Building
121 King Lam Street, Cheung Sha Wan
Kowloon, Hong Kong



SARTELCO® SISTEMI SRL

Via Torri Bianche, 1
20871 Vimercate (MB)

Tel. +39- 039- 62905.1 Fax. +39- 039- 62905.99
e-mail sistemi@sartelco.it Web www.sartelco.it