

NB1810-L4E-G

Industrial Router with LTE + GbE + SFP + 4x GbE + GNSS

High-performance and modular mobile router with Gigabit Ethernet and fiber ports to connect remote locations.



Keyfeatures

Mobile / Cellular	1x LTE, UMTS, GSM
SIM	2x Micro SIM
Ethernet	4x Gigabit Ethernet (4-Port Switch), 1x SFP/Gigabit Ethernet Combo, 1x Gigabit Ethernet
Extended Storage	1x SD Card
Serial / Fieldbus	1x RS-232/485
Positioning	Multi-GNSS
Operation Temperature	-40 °C to +70 °C
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates
Compliance	CE (RED)
Modularity	Extensions on request

Product description

The NB1810 is a powerful and robust cellular router designed for use in industrial environments.

Applications

- Condition Monitoring
- Industrial Security
- Factory Automation
- Remote Management
- Smart Buildings
- Point of Sale
- Smart Grid
- Oil & Gas
- Renewable Energy
- CCTV

Specifications

Mobile / Cellular	Standard	1x Multimode LTE, UMTS, GSM for EMEA 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B20 (800) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB FCC ID XPTYOBYL210
	Region Connectors SIM	Europe, Middle East and Africa (EMEA) 2x SMA female 2x Micro SIM - 3FF
Ethernet	Standard	1x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps 1x Gigabit Ethernet / SFP combo (software switchable) Ethernet standard 1000BASE-T, Auto MDIX SFP standard Depending on module, ask for supported modules Speed 10/100/1000 Mbps Combo port SFP or GbE interface activated (software switchable) 4x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps
	Connector	2x RJ45, 1x RJ45, 4x RJ45

Positioning	Standard	1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream
	Connector	1x SMA female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	1x RS-232/485 combo (software switchable) Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 1 Mbps Protocol EIA-485 Signals A, B Signal level Differential output voltage, loaded 1.5 VDC - 3.6 VDC Bit rate Up to 1 Mbps Termination 120 Ω for RS-485 configurable by software
	Connector	1x Terminal block header 3.5 mm (screw locking)
Extended Storage		SD Card Slot type microSD Speed (read / write) 600 kByte / s Application Store user and logging data of SDK or LXC applications SD card not included
System	Core	1.3 GHz dual-core, 1 GB RAM, 4 GB flash
	Module Slots	2x miniPCIe (PCIe + USB), 2x Extension (USB)
Software	Features	NetModule Router Software Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), logging Remote Management Manage and monitor devices with SNMP, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / soft-SIM support, multi-APN support, signal strength monitoring, dedicated bearers, GSM/CSFB calls Wireless LAN Client or Access Point mode, multi client support, multi / hidden SSID, WPA-PSK/WPA2-PSK, WPA-RADIUS, WPA-EAP-TLS, IEEE 802.11w, RADIUS accounting, CAPWAP Link Management Link prioritisation, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision Network Services DHCP Client, DNS server, email, SMS service, NTP Client, NTP server, DynDNS, SSH server, SNMP agent, HTTP/HTTPS/FTP server, voice gateway, SIP call routing, coovachilli hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, TCP-MSS clamping, STP/RSTP, bridging, LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, VLAN, PPPoE VPN OpenVPN, IPsec, PPTP, GRE, CSD dial-in Firewall Stateful firewall, connection tracking, NAT, masquerading, bridge filtering
	Licenses	GNSS Enabled service GNSS location service Server with JSON-, NMEA stream
Power	Input Voltage	12, 24, 48 VDC Nominal voltages 12, 24, 48 VDC Absolute voltages 12 VDC to 48 VDC (-25 % /+10 %)
	Connector Consumption	1x Terminal block header 3.5 mm (screw locking) 15 W (average), 22 W (max)
Mounting		DIN-Rail
Dimensions	W x H x D	Width 95 mm x height 128/140 mm x depth 121 mm
Weight		1100 g
Environment	Operating Temperature	-40°C to +70°C
	Ingress Protection Level	IP40

MTBF		220'000 h / 25.1 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS) Industrial
Order Code		NB1810-L4E-G
