

# NB800 UMTS

## Wall-Mounted Industrial Router with UMTS and Ethernet



### Applications

- Industrial IoT
- Smart Home
- ATM, POS
- CCTV
- Digital signage
- Electronic payment
- Preventive maintenance

**The NB800 enables robust Internet connection for vending machines or ticketing. Its modular design supports a wide range of protocols addressing the fast developing Internet of Things (IoT).**

The industrial grade router provides key technologies to access any kind of applications in the Internet, but also Intranet sites and remote stations which can be connected via its powerful VPN protocol suite including OpenVPN and IPsec.

The integrated modem supports UMTS networks and ensures WWAN connectivity. Ethernet and USB open further possibilities to integrate sensors and actuators easily into the network. A hardware shield concept brings additional flexibility to turn the NB800 into an application specific tailored device (OEM) or to follow the technology changes. The following shields are currently under development: Digital IOs, RS-232, RS-485, dual CAN, GNSS and LoRa concentrator.

The durable aluminum housing suitable for wall-mounting in combination with the supported temperature range -40 °C to 70 °C stands for its robustness. NB800 resists mechanical and thermal stress.

The router software is based on well proven components including an embedded Linux operating system and a wide range of communication and routing protocols as VLAN, Mobile IP, OSPF, BGP and RSTP. It's possible to run customer applications in a LXC Container. An SDK gives programmers a great tool to implementing all kind of applications with simple scripts. Data preprocessing can be done directly on the router, thus saving an additional IPC. Other features include a smart Link Manager for optimized cellular connections, Quality of Service (QoS) for an efficient data exchange, E-Mail and SMS for alarming and notifications, a web server and RADIUS authentication.

### Key Features


- Small form factor
- Price competitive
- Fanless
- UMTS/GSM
- Expandability by shields
- NetModule Router Software

### Performance

- 600 MHz CPU
- 100 Mbps routing performance

## Specifications

Mobile / Cellular	1 Multimode UMTS and GSM module 3G - UMTS/HSPA: B8(900MHz), B1(2100 MHz) 2G - GSM/GPRS/EDGE: B5(850 MHz), B8(900 MHz), B3(1800 MHz), B2(1900 MHz) Data rate: max. 21.6 Mbps downlink / 5.76 Mbps uplink (HSPA+) 1 SMA antenna connector 1 Micro SIM (3FF) ETSI TS 102 221 V9.0.0, Mini-UICC
Ethernet	1 Ethernet port, 10/100 Mbps, auto MDIX - Connector type: RJ45
USB	USB 2.0 Host Port, USB A connector type
Shields (planned)	Digital and analog I/O, RS-232/485, 2xCAN, GNSS Adv.
Storage	4GB internal
Power	Nominal Input Voltages: 12VDC (+/-20%), 24VDC (+/-20%) Average power consumption: 5W Connector type: 2 pin terminal block, 3.5 mm pitch
Environment	Operational temperature: -40 °C to +70 °C; Storage temperature: -40 °C to +85°C Ingress Protection Rating: IP40
MTBF	>440.000h depending on model
Dimensions	Width 85/111mm x height 32mm x depth 110mm, ca. 200g
Compliance	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), 2012/19/EU (WEEE), 1907/2006/EC (REACH)
Standards	EN 62368-1, EN 62311, EN 55024, EN 55032, EN 61000-6-2, EN 61000-6-3, EN 301 489-1, EN 301 489-7, EN 301 489-17, EN 301 489-24, EN 300 328, EN 301 511, EN 301 893, EN 301 908-1, EN 301 908-2, EN 301 908-13
Order numbers NB800-USu	(contact sales for more models, options or project specific adaptations) UMTS/GSM Router with USB



**SARTELCO® SISTEMI SRL**

Via Torri Bianche, 1  
20871 Vimercate (MB)

Tel. +39- 039- 62905.1 Fax. +39- 039- 62905.99  
e-mail [sistemi@sartelco.it](mailto:sistemi@sartelco.it) Web [www.sartelco.it](http://www.sartelco.it)

**NetModule AG**  
Meriedweg 11  
3172 Niederwangen

T +41 31 985 25 10  
F +41 31 985 25 11

Switzerland

**NetModule GmbH**  
Frankfurter Strasse 92  
65760 Eschborn

T +49 6196 77 99 79 0  
F +49 6196 77 99 79 9

Germany