



CFIP Phoenix

split mount radio system with capacity of up to 366 Mbps full duplex



- High Capacity Throughput supporting 256QAM modulation and 56 MHz channel bandwidth
- Modern components and latest technologies applied in CFIP Phoenix make it one of the most energy efficient equipment on the market
- Industrial grade design with fanless cooling system and split mount architecture
- Flexible TDM/IP architecture allows easy transition from TDM-only to hybrid or IP-only network
- Built-in managed Gigabit Ethernet switch, QoS, up to 4093 concurrent VLANs

Intended for classic telecom architecture CFIP Phoenix split mount system is designed to fit in a classic telecom architecture with a radio located outdoor and a sheltered indoor unit. CFIP Phoenix also enables transition from TDM networks to hybrid TDM/IP networks providing up to 20E1 + GigE. Total maximum capacity is up to 366 Mbps full duplex.



| | ETSI | FCC |
|------------------------|--|-------------------------------|
| Frequency Bands | 4/6/7/8/10/11/13/15/18 /23/26/32/38/42 GHz | 6/7/11/13/15/18/23/38 GHz |
| Channel Bandwidths | 3.5, 7, 14, 28, 40, 56 MHz | 5, 10, 20, 30, 40, 50, 56 MHz |
| Modulation | 4QAM, 16QAM, 32QAM, 64QAM, 128QAM, 256QAM with hitless ACM | |
| Capacity | up to 366 Mbps | |
| Configurations | 1+0, 1+1 (HSB, SD, FD), 2+0, 3+0, 4+0 Ethernet aggregation | |
| Ethernet | 4x 1000Base-T, RJ-45 | |
| E1/T1 | 20x E1/T1, RJ-45 | |
| Service ports | AUX RS-232, RSSI port for RSL, Serial port for MNGT configuration, EOW, 1+1 protection port, Alarm port | |
| Connection to ODU | N-Type Female | |
| Management | MIB, SNMP v1/v2c, Web GUI, Telnet, FTP/TFTP, Serial terminal | |
| Performance graphs | Rx level, Tx level, Radial MSE, LDPC decoder stress, Modem temperature, IDU temperature, ODU temperature, Power supply input voltage, Power supply power consumption, equalizer graph , uptime counter | |
| Ethernet switch | Managed Gigabit Ethernet Layer 2 | |
| QoS | 64 level DiffServ (DSCP) or 8 level 802.1p mapped in 4 prioritization queues with VLAN support | |
| VLAN support | 802.1Q (up to 4K VLAN entries) | |
| Spanning Tree | 802.1D-2004 RSTP, 802.1Q-2005 MSTP | |
| IDU Operational use | Conforms to ETSI EN 300 019 Class 3.1E, IP20, NEMA 1 | |
| Max. power consumption | for IDU: 20-30W for CFIP ODU: SP 13-27W, HP 21-39W | |

* Inquire SAF representative for more information



SARTELCO® SISTEMI SRL

Via Torri Bianche, 1
20871 Vimercate (MB)

Tel. +39- 039- 62905.1 Fax. +39- 039- 62905.99
e-mail sistemi@sartelco.it Web www.sartelco.it

For more detailed information about SAF products visit our website www.saftehnika.com or contact your SAF representative
Product features may vary between different models, configuration and all data are subjected to change without prior notice.

SAF Tehnika © 2015