

Antenna-Wall-L

Wall Antenna with LTE

Vertical polarization antenna for 4G, 3G, 2G networks



Keyfeatures

Cellular	LTE / UMTS / GSM
WiFi	2.4 GHz

Specifications

Mobile / Cellular	Standard	1 x LTE / UMTS / GSM LTE Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 13, 18, 19, 20, 25, 26, 27, 69 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 41, 53 UMTS Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 19, 20, 25, 26 - TDD Bands: 0, 1, 2, 3, 4, 5, 7 GSM Bands: 850, 900, 1800, 1900 Frequency 790 - 960, 1710 - 2170, 2400 - 2690
	Specification	Gain 1 dBi ± 0,5 dB 3 dBi ± 0,5 dB (WiFi 2.4) VSWR ≤ 2 typ. Impedance 50 Ohm Radiation omnidirectional azimuthal
	Connectors	1x SMA male fix connected 5m antenna cable

Mechanical	Dimensions	Diameter 148 mm Height 224 mm
	Weight	150 g
	Mounting	Bracket
	Color	black

Environment	Operating Temperature	-40°C to +85°C
	Ingress Protection Level	IP54

Certifications	Domain	Industrial
Extension Cables	Cellular	1 x fix connected / 5 m / SMA male
Other	Order Code	Antenna-Wall-L
