

Digi Connect[®] WAN GSM-R

Wireless WAN Gateway/Router for Railway

2G Wireless WAN cellular router provides wireless TCP/IP data communications via cellular GSM-R networks for railways.



Overview

The GSM-R network, owned and operated by several European railway operators, is part of the European Rail Traffic Management System (ERTMS). It provides a secure and reliable wireless infrastructure for communication with trains, railway signal equipment, and customer information displays.

The Digi Connect WAN GSM-R utilizes the GSM-R infrastructure to provide wireless device connectivity to Ethernet networks and serial devices. Its GPRS Class 10 cellular interface provides data rates up to 240 Kbps (100-130 Kbps typical).


Benefits of wireless communications via the Digi Connect WAN GSM-R include instant deployment, elimination of wiring costs, elimination of problems due to wire breaks and the ability to traverse firewalls. In addition, the Digi Connect WAN GSM-R offers the flexibility to move the connection anywhere within the coverage area of the railway operator's own free-of-charge data network.

Target Applications



Transportation

Application Highlight



Features/Benefits

- 2G (GSM-R) cellular router with 1 serial, 1 Ethernet port for wireless railway network connectivity
- 9-30VDC for diverse power input
- Web interface for easy centralized console configuration and statistics
- Digi Connectware[®] Manager enables remote management of large numbers of devices
- Unique Digi SureLink[™] maintains "always-on" wireless connection across unpredictable networks
- Programmable in Python for device customization



Specifications

Digi Connect® WAN GSM-R

Interfaces	
Serial	
Ports	1 RS-232/422/485 DB-9; Up to 230 Kbps throughput; Hardware and software flow control; Signal support for TXD, RXD, RTS, CTS, DTR, DSR, DCD
Ethernet	
Ports	1 RJ-45 10/100 Mbps 10Base-T (auto-sensing); Full or half duplex
Cellular	
GSM GPRS 12/EDGE 10	Fixed
Features	
Network Protocols	UDP/TCP, DHCP
Status LEDs	Ethernet, power on, cellular link/activity, signal strength (4 bars)
Software	Device-initiated patented RealPort COM port redirector and RFC 2217; Digi SureLink "always-on" connection; Python scripting; Custom development environment
Security	SSL, SSL/TLS, SSHv2, FIPS 197
Router/Firewall Features	NAT, NAT-T (NAT traversal) VPN tunneling, Port forwarding, VPN/GRE pass-through; Access control lists (IP filtering), IP pass-through, Virtual Router Redundancy Protocol (VRRP) per RFC 3768
VPN Features	IPsec with IKE/ISAKMP; Multiple tunnel support; DES, 3DES and up to 256-bit AES Encryption, Simple Certificate Enrollment Protocol (SCEP) for X.509 certificates
Management	HTTP/HTTPS, CLI or Telnet; Optional secure enterprise management via Digi Connectware Manager
Dimensions (L x W x H) and Weight	5.25 in (13.34 cm) x 3.35 in (8.51 cm) x 0.97 in (2.47 cm), 1.00 lb (0.45 kg)
RF Features	
Class	GPRS multi-slot class 10; 85 Kbps max (downlink)
Output Power	Class 4 (2W) at EGSM900; Class 1 (1W) at GSM1800
Frequency	Quadband GSM-R /EGSM 900/GSM 1800
Antenna	1 x 50 Ohm female SMA connector
Power Requirements	
Power Input	9-30 VDC
Power Supply	12VDC power supply for 0° C to 60° C (32° F to 140° F) with locking barrel connector included; Extended temperature power supply available
DC Power Consumption	Idle: 1.2W; Max: 3.4W
AC Power Consumption	Idle: 2.0W; Max: 5.8W
Surge Protection	4 kV burst (EFT) per-4-4; 2 kV surge per EN61000-4
Environmental	
Operating Temperature	-30° C to +75° C (-22° F to +167° F)
Relative Humidity	5 to 95% (non-condensing)
Ethernet Isolation	1500VAC min per IEEE 802.3/ANSI X 3.263
Serial Port Protection (ESD)	+15 kV air gap and +8 kV contact discharge per IEC 1000-4-2
Approvals	
Safety	UL 60950, CSA 22.2 No. 60950, EN60950
Emissions/Immunity	CE, FCC Part 15 Class A (FCC identifier GGL-R1902G), AS/NZS CISPR 22, EN55024, EN55022 Class A
Mobile Certifications - GSM/UMTS	PTCRB, NAPRD.03, GCF-CC, R&TTE, EN 301 511

Visit www.digi.com for part numbers.

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support

Digi International

877-912-3444
952-912-3444
info@digi.com

Digi International

France
+33-1-55-61-98-98
www.digi.fr

Digi International

KK
+81-3-5428-0261
www.digi-intl.co.jp

Digi International


(HK) Limited
+852-2833-1008
www.digi.cn

© 2008-2011 Digi International Inc.

Digi, Digi International, the Digi logo, the Making Wireless M2M Easy logo, Digi Connect, Digi Connectware, Digi SureLink and RealPort are trademarks or registered trademarks of Digi International Inc. in the United States and other countries worldwide. All other trademarks are the property of their respective owners. All other trademarks are the property of their respective owners.



91001477
B2/511



SARTELCO® SISTEMI SRL

Via Torri Bianche, 1
20871 Vimercate (MB)
Tel. +39-039-62905.1 Fax.
+39-039-62905.99

info: sistemi@sartelco.it
ordini/promozioni:
amministrazione@sartelco.it

www.sartelco.it