

100evo Series

maestro



empowering wireless

Easy to use, reliable, industrial modems

Maestro 100 Evolution series is the perfect solution for demanding M2M applications. Compact and fully featured, the Maestro 100evo series can easily be integrated into industrial application from electricity meters to intrusion alarms or vending machines. Maestro 100evo modems are GPRS quadband and full type approved, making them immediately usable worldwide. Renowned for their outstanding reliability, Maestro 100evo modems are the perfect devices to integrate in each of your projects facing tough conditions or extended lifetime requirements.

100evo Series



100evo Crystal : GPRS, plastic casing
(Transparent bitpipe)

100evo Lite : GPRS, Metal Casing,
(local config.)
+ Smart Pack Lite
+ 1 Digital Input

100evo IP : GPRS, Metal Casing,
(remote config.)
+ Smart Pack II
+ 1 Digital Input

100evo Advance : GPRS, Metal Casing, IDS
(Advance temperature)
+ Smart Pack II
+ 1 Digital Input
+ 1 Analog Input
+ Extended Temperature

Versatility

Maestro 100evo series provides different features regarding connectivity, intelligence or configuration software. You can thus get all the advantages of instant integration.



Smart
Pack II
BACK II



Technical information

Maestro 100evo modems are available in metal or plastic casing.



TECHNOLOGY	
GSM	Quadband
GPRS	Class 10
Voice/Data/Fax/SMS	✓
TCP/IP	Full TCP/IP Stack
INTERFACES	
SIM Plug-in card reader	1.8/3 V.
RS232 on 15 pin Sub-D connector	✓
Pin power supply connector	4 pin DC
SMA antenna connector (50 ohm)	✓
POWER SUPPLY	
Input voltage	6 to 32V DC
POWER CONSUMPTION	
GSM 850/900 (PCL 5)	203mA at 6V
DCS 1800/PCS 1900 (PCL0)	140mA at 6V
GPRS 850/900 CL10 (PCL5)	388mA at 6V
GPRS 1800/1900 CL10 (PCL0)	232mA at 6V
Idle consumption	45mA at 6V
Idle consumption (RS232 not connected)	18mA at 6V
Sleep Mode	4mA at 6V
CERTIFICATIONS/COMPLIANCES	
CE, GCF, RoHS Certification	
VOICE, DATA AND SMS FEATURES	
Data circuit asynchronous, transparent and non-transparent up to 14,400 bit/s ; Automatic fax group 3 (Class 1 and Class 2) ; MNP2, V.42bis ; Text and PDU SMS ; Point to point SMS (MT/MO) ; UCS2 Character Set Management	
FUNCTIONAL FEATURES	
AT command set (GSM 07.05, GSM 07.07 and Wavecom)	> 300

Distributor's Contact

FEATURES/PRODUCTS	M100evo Crystal	M100evo Lite	M100evo IP	M100evo Advanced
Input - Digital	N/A	1	1	1
Input - Analog		N/A		1
Download Over The Air		N/A		Optional
Autorestore - timer reset			✓	
OTHER FEATURES				
Operating status LED			✓	
Casing	Plastic			Metal

DIMENSIONS			
Size (mm)	88x60x26		90x72x23
Weight (g)	70		100
TEMPERATURE RANGE			
Operating / Storage	-30~+75 °C / -40~+85 °C		-30~+85 °C / -40~+85 °C

OPTIONAL ACCESSORIES (ADDITIONAL ACCESSORIES ARE ALSO AVAILABLE UPON REQUEST)				
GSM antenna 900/1800 Mhz	✓	✓	✓	✓
GSM antenna 850/1900 Mhz	✓	✓	✓	✓
RS232 cable interface	✓	✓	✓	✓
Din Clip (metal casing only)	N/A	✓	✓	✓

SMART PACK II FEATURES				
I/O Monitoring		✓	✓	✓
GPRS and IP configuration		✓	✓	✓
Call Screening	N/A	Smart Pack Lite (Local Configuration)	✓	✓
DynDNS			✓	✓
Remote AT Command			✓	✓
Ping			✓	✓
Status check and monitoring			✓	✓

Maestro Wireless Solutions Ltd
3603-9, 36/F
118 Connaught Road West
Hong Kong
Tel: (852) 2869 0688
Fax: (852) 2525 4701
contact@maestro-wireless.com
www.maestro-wireless.com

Copyright Maestro Wireless Solutions Limited. We reserve the right at any time and without prior notice to modify or improve the modems and the services offered, the same applies to the accessories which could also be withdrawn.



SARTELCO® SISTEMI SRL

Via Torri Bianche, 1
20871 Vimercate (MB)
Tel. +39-039-62905.1 Fax.
+39-039-62905.99
info: sistemi@sartelco.it
ordini/promozioni:
amministrazione@sartelco.it
www.sartelco.it

