

Antenna-Roof-2L2WG

Roof Antenna with MIMO LTE + MIMO WLAN + GNSS

Omnidirectional combo antenna with linear polarization for signal enhancement in 4G, 3G, 2G and WLAN networks and right-hand circular polarization for the active GPS antenna.



Keyfeatures

WiFi / WLAN	MIMO 2.4 / 5 GHz
Cellular	MIMO LTE / UMTS / GSM
GNSS	active

Specifications

Mobile / Cellular	Standard	2 x LTE / UMTS / GSM LTE Bands: 1, 2, 3, 4, 5, 7, 8, 10, 12, 13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28, 29, 30, 65, 66, 67, 68, 69, 70, 85 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53 UMTS Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 19, 20, 25, 26 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40 GSM Bands: 710, 750, 810 T-GSM, 850, 900 P, 900 E, 900 R, 1800 DCS, 1900 PCS Bands 710, 750, 810 T-GSM, 850, 900 P, 900 E, 900 R, 1800 DCS, 1900 PCS Frequency 704 - 960, 1710 - 2690
	Specification	Gain 6.9dBi@700~960MHz (1m Cable) 4.0dBi@1710~2170MHz (1m Cable) 2.7dBi@2300~2690MHz (1m Cable) VSWR ≤ 2.2 typ. Impedance 50 Ohm Radiation omnidirectional
	Connectors	2x SMA male fix connected 3m antenna cable
WiFi / WLAN	Standards	2 x Dual-band WLAN 2.4/5 GHz Frequency 2400 - 2500, 5100 - 5850
	Specification	Gain 3,9 dBi (WLAN 2.4) / 3,3 dBi (WLAN 5) VSWR ≤ 1,7 typ. Impedance 50 Ohm Radiation omnidirectional
	Connectors	2x SMA male fix connected 3m antenna cable
GNSS	Standards	1 x GPS / Galileo / GLONASS / BeiDou Type active Frequency 1532 - 1618
	Specification	Gain 27 dBi VSWR ≤ 1,5 typ. Impedance 50 Ohm Radiation omnidirectional
	Amplifier	Power 3 - 5.5 V Current 6,1 mA - 13 mA Gain 25 dB typ.
	Connectors	1x SMA male fix connected 3m antenna cable
Mechanical	Dimensions	Diameter 110 mm Height 40 mm
	Weight	750 g
	Mounting	Rooftop with screws
	Color	black

Environment	Operating Temperature Ingress Protection Level	-40°C to +80°C IP67
Certifications	Compliance Domain	RoHS, REACH Industrial
Extension Cables	Cellular WLAN GNSS	2 x fix connected / 3 m / SMA male 2 x fix connected / 3 m / SMA male 1 x fix connected / 3 m / SMA male
Other	Order Code	Antenna-Roof-2L2WG
