

Tags and badges



IDENTIFY LOCATE MEASURE



An industrial beacon with buzzer with multiple uses: help in finding equipment,

sound alert for worker safety!

- Extended transmission range: up to 500m (open field) •
- Battery lifespan: up to 17 years •
- Sound alarm / Buzzer •
- Built-in LED: Pick to light system •
- Robust industrial case IP65 waterproof •
- Built-in NFC chip •

TECHNICAL SPECIFICATIONS	
Operating modes	Advertising mode: periodic data transmissionConnected mode: LED indicator command and BUZZER alarm command.Note: simultaneous use of LED and BUZZER is not possible
Parameters and configuration	 Interface/protocol NFC (Type 2) Configuration: Device Manager/ Mobile Manager application (Windows / Android) Activation / deactivation BLE advertising name (15 characters max.) and transmit power Transmission period (0,1 sec to 10 sec - configurable in seconds) Format: ELA ID, iBeacon (Apple), Eddystone (Google)
Sensor option / performances	Buzzer characteristics: 4 kHz / 77 dB @ 8 cm
Frequency	2.4 GHz – BLE channels
Output power	Up to +4 dBm
Range	Up to 500 meters open field (+4 dBm)
Power supply	3 VDC – Internal lithium battery
Battery life	 Up to 17 years Battery voltage reading command using Connected mode 15% remaining battery warning *For more detailed battery lifetime specification please refer to autonomy spec sheet
Operating temperature	-30°C to +70°C
Housing	Ø 57mm base - Thickness 20mm IP68 Waterproof - Weight 36g DELRIN (POM C) material – Food Grade (90/128/EEC)
Standards	CE (Europe): EN 300 328/EN 300 330, EN 301 489, EN 62311, EN 62368 FCC (USA): FCC PART 15 ISED (Canada): RSS-247/ICES-003 RoHS certified
Accessories	Double-sided direct fixation of the tag: PUCK STICKER (ACIOM188) Tag support: PUCK HOLDER STICKER (BOT0126)

Ref. IDF31245