

## IDENTIFY LOCATE MEASURE

Tags and badges



## The beacon identifier in watch format for simple and comfortable use!

- Very high range: up to 200 meters (open field)
- High lifecycle: up to 5 years
- Pick to light system: integrated LED
- Robust industrial casing IP55 waterproof
- Integrated NFC chipset



TECHNICAL SPECIFICATIONS	
Operating modes	Advertising mode: periodic transmission of identifier data (beacon mode)  Connected mode: LED indicator (ON/OFF command)
Parameters and configuration	Interface/protocol NFC (Type 2) Configuration: Device Manager Suite / Mobile application (Windows / Android)
Frequency	2.4 GHz - BLE channels
Output power	Up to +4 dBm
Range	Up to 200 meters open field (+4 dBm)
Power supply	3 VDC - Internal lithium battery
Battery life	<ul> <li>Up to 5 years (ELA ID), 4,9 years (iBeacon), 5 years (Eddystone) *</li> <li>Battery voltage reading command using Connected mode</li> <li>15% remaining battery warning</li> <li>*For more detailed battery lifetime specification please refer to autonomy spec sheet</li> </ul>
Operating temperature	-20°C to +55°C
Housing	47x37,1x12,5 mm IP55 Waterproof - Weight 11g Polyamide (Nylon) PA12 material
Standards	CE (Europe): EN 300 328/EN 300 330, EN 301 489, EN 62311, EN 62368 FCC (USA): FCC PART 15 ISED (Canada): RSS-247/ICES-003 RoHS certified
Accessories	WATCH STICKER (ACIOM205)